

WALK-BEHIND ROLLER



TWO IN ONE

▶ TRULY MULTI-PURPOSE

Adjustable weights allow quick switching from working on asphalt to loose substrate. Designed to excel in both applications, this fully hydraulic machine is the most versatile solution for your job site.





▶ ASPHALT READY

Water sprinkler and 60-liter tank come as standard – effectively preventing asphalt from caking on the drums.



▶ ADVANCED TECHNOLOGY

Durable, fully hydraulic drive allows for precise speed adjustments and improves the machine's uptime and performance.



PERFORMANCE

EASY TO USE



▶ PRACTICAL SOLUTION

Built to meet the challenges of every job site: full side clearance allows you to work in close proximity to walls, corners and curbs. Additional handy features – like automatic parking brake or dead-man handle – are designed around the way you work.


To further enhance the roller's versatility, adjustable eccentric weights allow the operator to choose between high and low amplitude settings. While high amplitude allows working on loose sub-structures, low amplitude is perfect for compacting asphalt.



▶ ACCESSIBLE TO EVERYONE

Bobcat walk-behind rollers are equipped with dead-man's handle as standard, and an additional mechanical safety button in the back that stops reverse movement when pushed. A hydraulic parking break and a limited reverse speed of 2.5 km/hour makes operating the machine easy and safe, even for less experienced operators.







0.5 mm amplitude for sub-structure applications



▶ COMFORTABLE GRIP

Carefully designed guide handle features several grip options and ergonomic height adjustments to suit the needs of every operator. Optimized for control and comfort, the whole handle is suspended, which further reduces vibration levels.



EASY SERVICING

A day in the shop doesn't earn you a cent. To make daily maintenance as simple as possible, we've eliminated the need to use any special tools. All service points are easily accessible and intuitively located.

WALK-BEHIND ROLLER



APPLICATIONS

A small machine tackling big challenges. Bobcat's walk-behind roller is an exceptionally versatile machine thanks to its high productivity and adjustable performance. After all, it's not the size – it's how many ways you can use it.

- Earthwork and asphalt applications
- Sidewalk / cycle paths construction / repair
- Sport grounds
- Agricultural roads construction / maintenance
- Forest road construction / maintenance



Bobcat's construction equipment has always set the standard for durability and reliability. The selection of high-quality components and protective covers is made to keep our walk-behind roller in the field, day after day.



OPTIONS

| OPTIONS | | | |
|---------------------------------------|----------|----------|--|
| | HATZ | YANMAR | |
| 60 L Water tank with sprinkler system | Standard | Standard | |
| Scrapers on front and back drum | Standard | Standard | |
| Operating hour meter | • | • | |
| Protection frame in front | • | • | |
| Electric starter | • | Standard | |





ALWAYS ON TIME

Vibration-activated hour meter can be fitted on the walk-behind roller to help you monitor working hours and ensure that maintenance needs are met.


■ ELECTRIC STARTER


Hatz engine version can be equipped with an electric starter for an effortless beginning to every shift (standard on Yanmar model). No need to crank the machine before work anymore.




SPECIFICATIONS

| SPECIFICATIONS | | | | |
|---------------------------------|------------|--------------|--|--|
| | WR65 | | | |
| WEIGHT & DIMENSIONS | HATZ | YANMAR | | |
| Machine weight | 719 kg | 712 kg | | |
| Machine weight with e-start | 738 kg | 712 kg | | |
| A Machine length | 2 288 mm | | | |
| B Wheelbase | 500 mm | | | |
| C Drum diameter | 400 mm | | | |
| D Machine height | 1 110 mm | | | |
| E Transport height | 1 835 mm | | | |
| F Machine width | 720 mm | | | |
| G Drum width | 650 mm | | | |
| ENGINE | | | | |
| Engine | Hatz 1D42S | Yanmar L100N | | |
| Fuel | Diesel | | | |
| Engine output | 6.1 kW | | | |
| Fuel consumption | 1.7 l/h | 1.2 l/h | | |
| COMPACTION FORCES | | | | |
| Max. vibration frequency | 60 Hz | | | |
| Centrifugal force | 11/21 kN | | | |
| Linear pressure | 5.7 kg/cm | 5.5 kg/cm | | |
| Amplitude | 0.3/0.5 mm | | | |
| Max. compaction depth (soil) | 20/15 cm | | | |
| Max. compaction depth (sand) | 30/25 cm | | | |
| MISCELLANEOUS | | | | |
| Speed (forward) | 4 km/h | | | |
| Speed (backward) | 2.5 km/h | | | |
| Gradeability with vibration | 25% | | | |
| gGradeability without vibration | 44% | | | |
| Fuel tank capacity | 51 | 4.7 l | | |
| Hydraulic oil capacity | 20 I | | | |
| Water tank capacity | 60 I | | | |















Bobcat is a Doosan Company.Doosan is a global leader in construction equipment, power & water solutions, engines, and engineering proudly serving customers and communities for more than a century. I Bobcat and the Bobcat logo are registered trademarks of Bobcat Company in the United States and various other countries. ©2021 Bobcat Company. All Rights Reserved.





GETAQUOTE

Simply click the button or scan the QR code below to access our quote request form.

We will contact you as soon as possible. Thank you!



REQUEST QUOTE